



3 different mounting
positions possible

*Each kit includes three sets of
the hardware shown.*

SPECIFICATIONS

For patents see www.cf-pat.com

General	PIM Shield Cable Support Bars provide a low passive intermodulation mounting system to secure multiple Hybrid or Plastic Snap-ins (sold separately) in high risk PIM zones. The 901166-02-3 kit includes 3x 900352-02 Pole Mount Kit and 3x 900354 Extra Bar Kit combined together into a convenient site pack for 3-sector sites.
Grip range	2.37-inch to 4.5-inch OD pipe (2-inch to 4-inch nominal pipe)
Snap-In mounting holes	26 snap-in mounting holes per installation, 0.75-inch diameter
Bar dimensions	2 bars per installation, 19.0-inch x 3.9-inch x 0.14-inch thick
Hardware size	1/2-13 UNC, 18-inch Threaded Rod length
System PIM performance	IM3 <-100 dBm when tested in accordance with IEC 62037-8, near field test, 2x 20W test tones, while subjected to dynamic stimulus. To achieve specified PIM performance, torque hardware to 20 FT-LB (ConcealFab tool 900413)
Material	Galvanized Steel
Operating temperature	-40°C to +70°C
Shipping dimensions	6.5-inch x 4.5-inch x 20-inch
Shipping weight	29.5 lb.