



5 different mounting positions possible

*Each kit includes three sets of the hardware shown.*

## SPECIFICATIONS

*For patents see [www.cf-pat.com](http://www.cf-pat.com)*

<b>General</b>	PIM Shield Cable Support Bars provide a low passive intermodulation mounting system to secure multiple Hybrid or Plastic Snap-ins (sold separately) in high risk PIM zones. The 901167-02-3 kit includes 3x 900353-02 Pole Mount Kit and 3x 900355 Extra Bar Kit combined together into a convenient site pack for 3-sector sites.
<b>Grip range</b>	2.37-inch to 4.5-inch OD pipe (2-inch to 4-inch nominal pipe)
<b>Snap-In mounting holes</b>	44 snap-in mounting holes per installation, 0.75-inch diameter
<b>Bar dimensions</b>	2 bars per installation, 30.5 -inch x 3.9-inch x 0.14-inch thick
<b>Hardware size</b>	1/2-13 UNC, 18-inch Threaded Rod length
<b>System PIM performance</b>	IM3 <-100 dBm when tested in accordance with IEC 62037-8, near field test, 2x 20W test tones, while subjected to dynamic stimulus. To achieve specified PIM performance, torque hardware to 20 FT-LB (ConcealFab tool 900413)
<b>Material</b>	Galvanized Steel
<b>Operating temperature</b>	-40°C to +70°C
<b>Shipping dimensions</b>	6.5-inch x 4.5-inch x 32-inch
<b>Shipping weight</b>	39.0 lb.