



SPECIFICATIONS

For patents see www.cf-pat.com

General	PIM Shield Cable Support Rails provide a low passive intermodulation mounting system to secure multiple Cable Support Blocks (sold separately) in high risk PIM zones. The Pole Mount Kit includes one rail plus the hardware required to secure the rail to a pole. An Extra Rail Kit can be added (sold separately) to double the number of connection points.
Grip range	2.37-inch to 4.5-inch OD pipe (2-inch to 4-inch nominal pipe)
Rail dimensions	12.0-inch x 1.5-inch x 1.5-inch
Pole mounting hardware	3/8-16 UNC, Galvanized steel
Rail attachment hardware	M10-1.5, Galvanized steel
System PIM performance	IM3 <-100 dBm when tested in accordance with proposed IEC 62037-8, near field test, 2x 20W test tones, while subjected to dynamic stimulus. To achieve specified PIM performance, torque all 3/8-inch hardware to 10 FT-LB and all M10 hardware to 15 FT-LB.
Rail Material	Extruded aluminum with clear anodize finish
Pole bracket material	Galvanized steel
Operating temperature	-40°C to +70°C
Case dimensions	11.0-inch x 13.0-inch x 8.5-inch
Case weight	41 lb.
Qty per case	10