



### SPECIFICATIONS

For patents see [www.cf-pat.com](http://www.cf-pat.com)

<b>General</b>	PIM Shield Cable Support Rails provide a low passive intermodulation mounting system to secure multiple Cable Support Blocks (sold separately) in high risk PIM zones. The Rail Kit includes one extruded aluminum rail plus the hardware required to secure the rail to a galvanized steel Pole Mount Kit or Wall Mount Kit (sold separately).
<b>Rail dimensions</b>	24.0-inch x 1.5-inch x 1.5-inch
<b>Rail attachment hardware</b>	M10-1.5 x 30 mm, galvanized steel
<b>System PIM performance (when installed at next higher assembly)</b>	IM3 <-100 dBm when tested in accordance with proposed IEC 62037-8, near field test, 2x 20W test tones, while subjected to dynamic stimulus. To achieve specified PIM performance, torque all M10 hardware to 15 FT- LB. (ConcealFab tool 900412)
<b>Rail material</b>	Extruded aluminum with clear anodize finish
<b>Channel runner material</b>	UV stable, glass filled Nylon
<b>Operating temperature</b>	-40°C to +70°C
<b>Case dimensions</b>	9.5-inch x 6-inch x 27-inch
<b>Case weight</b>	14.2 lb.
<b>Qty per case</b>	10